



BOILER CONNECTIONS		RATINGS & CAPACITIES		LTR	DATE	REVISION		BY	REPRESENTATIVE:
A.(1) STEAM OUTLET	4" 300# FLG	RATED INPUT	2000 MBH						?
B.(2) LWCO	1" NPT	GROSS OUTPUT	1660 MBH						
C.(1) ALWCO	3/4" NPT	DESIGN PRESSURE	150 PSIG STEAM						
D.(1) SAFETY VALVE	1" NPT	STEAM (FROM & AT 212°F)	1592 Lbs/Hr						
E.(1) BOILER BLOWDOWN	1" NPT	HEAT RELEASE: (FURNACE ONLY)	157,793 BTU/CuFt						
F.(1) PRESSURE TROL	3/4" NPT	HEATING SURFACE (ASME)	139 SqFt						
G.(1) FEEDWATER	1" NPT	FURNACE HEATING SURFACE	17.51 SqFt						
H.(4) INSPECTION	2" NPT	FURNACE VOLUME	12.67 CuFt						
J.(1) SIGHTPORT	2" PIPE								
K.(1) SURFACE BLOWDOWN	1" NPT								
L.(2) SIGHT GLASS	1/2" NPT	STEAMING VOLUME	7.29 CuFt						
M.(1) OVERFLOW	1" NPT	STEAM RELEASE AREA	6.25 SqFt						
N.( )		WATER CAPACITY:							
P.( )		(FULL)	186.1 Gals @ 1,548 Lbs						
Q.( )		(NWL)	131.6 Gals @ 1,094 Lbs						
R.( )		SHIPPING WEIGHT:	2,700 Lbs						
S.( )									

  

NOTES			
1. ALL CONTROLS MOUNTED AS PER SPECIFICATION SHEET. 2. SPECIFICATION SHEET TAKES PRIORITY OVER R & D SHEET. 3. BOILER DESIGN CODE ASME SECTION I. 4. BOILER INSULATED & COVERED W/22 GA. STEEL JACKET. 5. ALL DIMENSIONS ARE ±1/2" UNLESS OTHERWISE NOTED.			

  

	CHECKED BY	DATE
	DRAWN BY	DATE
TRIAD	BOILER MODEL 2000-HP	
SCALE 1/26	DRAWING No ?	

  

THIS DRAWING IS THE PROPERTY OF SUPERIOR BOILER WORKS & SHALL NOT BE REPRODUCED IN PART OR IN WHOLE, & NONE OF ITS INFORMATION SHALL BE REVEALED WITHOUT PERMISSION OR TO THE DETRIMENT OF THE OWNER. IT MUST BE RETURNED UPON REQUEST.
---